

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

marked T 20 S R 10 W Sec 20 B T.

Fir, 12 ins. diam., bears N.33 $\frac{1}{2}$ °E., dist. 75 lks.,

marked T 20 S R 10 W Sec 21 B T.

Alder, 6 ins. diam., bears S.39 $\frac{1}{2}$ °W., dist. 59 lks.,

marked T 20 S R 10 W Sec 29 B T.

Thence I run

N.89°39'E., on true line, bet. secs. 21 and 28.

Va.19°E.

Over broken hilly land.

39.90 Set post, 4 ft. long, 3 $\frac{1}{2}$  ins. sq., 24 ins. in ground,

for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on N. face; from which a

Chittem tree, 6 ins. diam., bears N.20°E., dist. 64

lks., marked  $\frac{1}{4}$  S B T.

Hemlock, 11 ins. diam., bears S.40°W., dist. 71 lks.,

marked  $\frac{1}{4}$  S B T.

56.00 Top of ridge, course NW.; descend.

79.90 Cross canyon to cor. of secs. 21, 22, 27, and 28.

Sept. 25, 1892.

From cor. of secs. 28, 29, 32, and 33, which is a stone,

20x10x8 ins., 6 ins. above ground, marked 1 notch on

S. and 4 notches on E. edges; from which an

Alder, 20 ins. diam., bears N.82°W., dist. 34 lks.,

marked T 20 S R 10 W Sec 29 B T.

I run N.3°W., on random line, bet. secs. 28 and 29.

Va.19°E.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.30 Intersect at cor. of secs. 20, 21, 28, and 29.

Thence I run

S.3°E., on true line, bet. secs. 28 and 29.

Va.19°E.

Over hilly broken ground.

40.30 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for

$\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on W. face; from which a

Maple, 7 ins. diam., bears N.27°E., dist. 74 lks.,