

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

Fir, 10 ins. diam., bears S.60°W., dist. 43 lks.,
marked T 20 S R 10 W Sec 21 B T.
Sept. 27, 1892.

From cor. of secs. 15, 16, 21, and 22, I run
S.89°25'E., on random line, bet. secs. 15 and 22.
Va.19°E.

40.00 Set temp. 1/4 sec. cor.
80.57 Intersect E. bdy. of Sec., 22 lks. S. of cor. of secs.
14, 15, 22, and 23.

Thence I run
N.89°34'W., on true line, bet. secs. 15 and 22.
Va.19°E.

Ascend.

25.00 Top of hill and a chittem tree, 6 ins. diam. on line,
marked 2 notches on E. and W. sides.

Descend.

40.28 1/2 On N. face of hill.
Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground,
for 1/4 sec. cor., marked 1/4 S on N. face; from which a
Fir, 11 ins. diam., bears N.50°W., dist. 63 lks.,
marked 1/4 S B T.
Hemlock, 9 ins. diam., bears S.76°W., dist. 74 lks.,
marked 1/4 S B T.

68.00 Head of gulch.
80.57 To cor. of secs. 15, 16, 21, and 22.

Sept. 27, 1892.

From cor. of secs. 15, 16, 21, and 22, I run
North 2' W., bet. secs. 15 and 16.
Va.19°E.

Ascend.

18.00 Top of ridge, course SW.; descend.
30.00 Canyon, course SW.; ascend.
40.00 Top of ridge, course NE.; descend.