

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

marked $\frac{1}{4}$ S B T.

Fir, 9 ins. diam., bears S.69 $\frac{1}{2}$ °E., dist. 58 lks.,

marked $\frac{1}{4}$ S B T.

Descend.

70.00 Creek, 10 lks. wide, course W.; ascend.

80.45 Cor. of secs. 16, 17, 20, and 21.

Oct. 3, 1892.

From cor. of secs. 8, 9, 16, and 17, I run

N.89°52'E., on random line, bet. secs. 9 and 16.

Va.19°E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect East bdy. of Sec., 10 lks. S. of cor. of secs. 9, 10, 15, and 16.

Thence I run

South 89°48'West, on true line, bet. secs. 9 and 16.

Va.19°E.

Ascend.

15.00 Top of ridge, course NE.; descend.

40.00 On S. slope of hill.

Set post, 4 ft. long, 3 $\frac{1}{2}$ ins. square, 24 ins. in ground,

for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which a

Fir, 25 ins. diam., bears N.17°W., dist. 66 lks.,

marked $\frac{1}{4}$ S B T.

Fir, 15 ins. diam., bears S.29°E., dist. 56 lks.,

marked $\frac{1}{4}$ S B T.

70.00 Canyon, course SW.; ascend.

79.90 Cor. of secs. 8, 9, 16, and 17.

Oct. 4, 1892.

From cor. of secs. 4, 5, 8, and 9, which is a post, 2 $\frac{1}{2}$

ft. above ground, marked T 20 S Sec 4 on NE., R 10 W

Sec 9 on SE., Sec 8 on SW., Sec 5 on NW. faces, with 5

notches on S. and 4 on E. edges; from which an

Alder, 10 ins. diam., bears N.72°E., dist. 35 lks.,