

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 10 W.

CHAINS

N.89°41'E., on true line, bet. secs. 7 and 18.

Va.19½°E.

Descend.

- 7.00 Branch, 3 lks. wide, course E.; ascend.
- 11.00 Top of hill; descend.
- 41.35 Creek, 10 lks. wide, course SE.
- Set post, 4 ft. long, 3½ ins. sq., 24 ins. in ground, for ¼ sec. cor., marked ¼ S on N. face; from which a
- Fir, 9 ins. diam., bears N.61°W., dist. 70 lks.,  
marked ¼ S B T.
- Fir, 10 ins. diam., bears S.34°E., dist. 80 lks.,  
marked ¼ S B T.
- 81.35 Along S. slope of hill, to the cor. of secs. 7, 8, 17,  
and 18.

Oct. 9, 1892.

From cor. of secs. 5, 6, 7, and 8, which is a post, 3 ins. sq., firmly set in ground, marked T 20 S Sec 5 on NE., R 10 W Sec 8 on SE., Sec 7 on SW., Sec 6 on NW. faces, with 5 notches on S. and E. edges; from which a

Maple, 4 ins. diam., bears N.69½°E., dist. 33 lks.,  
marked T 20 S R 10 W Sec 5 B T.

Fir, 16 ins. diam., bears S.68°E., dist. 103 lks.,  
marked T 20 S R 10 W Sec 8 B T.

Fir, 48 ins. diam., bears S.65°W., dist. 76 lks.,  
marked T 20 S R 10 W Sec 7 B T.

Fir, 48 ins. diam., bears N.42°W., dist. 111 lks.,  
marked T 20 S R 10 W Sec 6 B T.

Thence I. run

S.89°41'W., on random line, bet. secs. 6 and 7.

Va.19½°E.

- 40.00 Set temp. ¼ sec. cor.
- 81.55 Intersect W. bdy. of Tp., 40 lks. S. of cor. of secs. 6, 7, 1, and 12, which is a post, marked T 20 S Sec 6 on NE., R 10 W Sec 7 on SE., R 11 W Sec 12 on SW., Sec