

Subdivisions of T. 20 S., R. 10 W.

CHAINS

1 on NW. faces, with 5 notches on S., 1 notch on N. edges; from which a

Maple, 8 ins. diam., bears N.45°E., dist. 30 lks.,
marked T 20 S R 10 W Sec 6 B T.

Maple, 24 ins. diam., bears S.89°E., dist. 30 lks.,
marked T 20 S R 10 W Sec 7 B T.

Fir, 4 ins. diam., bears N.21°W., dist. 47 lks.,
marked T 20 S R 11 W Sec 1 B T.

Alder, 3 ins. diam., bears S.64°W., dist. 117 lks.,
marked T 20 S R 11 W Sec 12 B T.

Thence I run N.89°58'E., on true line, bet. secs. 6 and 7.
Va.19½°E.

Ascend.

41.55 Top of high ridge, course N. +250

Set post, 4 ft. long, 3½ ins. sq., 24 ins. in the ground,
for ¼ sec. cor., marked ¼ S on N. face; from which a
Maple, 4 ins. diam., bears N.40°E., dist. 75 lks.,
marked ¼ S B T.

Maple, 5 ins. diam., bears S.66°E., dist. 80 lks.,
marked ¼ S B T.

Descend.

50.00 Canyon, course N.; ascend. -250

70.00 Top of high ridge, course S.; descend E. slope of hill. +200

81.55 To cor. of secs. 5, 6, 7, and 8.

Oct. 10, 1892.

Resurvey of West Bdy. of T. 20 S., R. 10 W.
by Nathaniel Martin under Contract 599 dated June 20, 1892.

Resurvey of West Bdy. commenced Nov. 4, 1894.

I begin at the established cor. to secs. 25, 36, 30, and
31, Rgs. 10 and 11 West, which is a sandstone, 14x11x6
ins., 10 ins. in the ground, marked with 1 notch on S.
and 5 notches on N. edges; from which a

Maple, 5 ins. diam., bears N.37°W., 38 lks. dist.,
marked T 20 S R 11 W S 25 B T.