

County Surveyor's Record, Douglas County, Oregon

Resurvey West Bdy. of T. 20 S., R. 10 W.

CHAINS

A maple, 7 ins. diam., bears N.45°E., 69 lks. dist., marked T 20 S R 10 W S 30 B T.

Maple, 18 ins. diam., bears S.35°W., 60 lks. dist., marked T 20 S R 11 W S 36 B T.

A hazel, 3 ins. diam., bears S.15°E., 35 lks. dist., marked T 20 S R 10 W S 31 B T.

Thence I run

North along established line bet. secs. 25 and 30.

Va.19°45'E.

Descend E. slope.

- 4.75 Stream, 6 lks. wide, course SE. and ascend spur.
- 6.50 Top of spur, course S. & SE. along E. slope. +50
- 14.00 A hollow; fir, 30 ins. diam. on line, which I marked with 2 notches on N. & S. sides.
- 23.50 Ridge, c S.25°W.; along N. slope. +350
- 30.00 Canyon, c S.20°W. & ascend. -50
- 36.00 Ridge, c E. & W.; along E. slope. +300
- 40.00 Here I made diligent search for the 1/4 sec. cor. Failing to find any traces of it, I, therefore, set a post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for 1/4 sec. cor., marked 1/4 S on W. face; from which
 - A fir, 10 ins. diam., bears S.72°30'E., 40 lks. dist., marked 1/4 S B T.
 - A dead fir, 40 ins. diam., bears N.20°30'W., 25 lks. dist., marked 1/4 S B T.
- 45.50 Stream, 4 lks. wide, c SE.
- 53.00 Spur, c SE.
- 55.00 A dead fir, 48 ins. diam. on line, I marked with 2 notches on N. and S. sides.
- 57.00 Spur, c NE. and descend steep.
- 61.00 Canyon, c NE. and ascend. -400
- 64.50 Spur, c NE. and descend.
- 66.00 Canyon, c NE.
- 75.00 Ridge, c N.20°E.
- 80.50 The cor. on N. bdy. of Sec. 30 set by me Sept. 1892 bears