

County Surveyor's Record, Douglas County, Oregon

Resurvey of West Bdy. of T. 20 S., R. 10 W.

CHAINS

cor.; from which a  
 Willow, 3 ins. diam., bears N.3°E., 4 lks. dist.,  
 marked  $\frac{1}{4}$  S B T.  
 A willow, 3 ins. diam., bears S.5°W., 10 lks. dist.,  
 marked  $\frac{1}{4}$  S B T.  
 64.50 Stream, 15 lks. wide, c E. and ascend.  
 75.50 Top of spur, c E.  
 80.10 The temp. cor. set by me Sept. 1892 at the end of 80.00  
 chs. on the N. bdy. of Sec. 7 bears N.89°58'E., 3.75  
 chs. dist.; I continued this line S.89°58'W., and at  
 point of intersection  
 Set a stone, 10x8x8, 7 ins. in ground for closing corner  
 to secs. 6 and 7, marked with C C and 5 notches on S.  
 and 1 notch on N. faces and raised mound of stone, 30  
 in. high and 24 in. base alongside. Pits impracticable.

North on W. bdy. of Sec. 6.

Va.20°E.

4.50 The established cor. to secs. 1, 6, 7, and 12, which is a  
 post, 4 ins. sq., firmly set 2½ ft. above ground, marked  
 T 20 S Sec 6 on NE., R 10 W Sec 7 on SE., R 11 W Sec 12  
 on SW., Sec 1 on NW. faces, with 5 notches on S. and 1  
 on N. edges; from which a  
 Maple, 8 ins. diam., bears N.45°E., 30 lks. dist.,  
 marked T 20 S R 10 W Sec 6 B T.  
 Maple, 24 ins. diam., bears S.89°E., 30 lks. dist.,  
 marked T 20 S R 10 W Sec 7 B T.  
 Alder, 4 ins. diam., bears S.64°W., 117 lks. dist.,  
 marked T 20 S R 11 W Sec 1 B T.  
 Fir, 4 ins. diam., bears N.20°W., 47 lks. dist.;  
 marked T 20 S R 11 W Sec 1 B T.  
 I destroyed all marks relating to R. 10 W.  
 4.75 Canyon, c N.80°E.; ascend.  
 13.00 Spur, c E.; descend.