

Resurvey Portion North Bdy., T. 21 S., R. 10 W.

CHAINS

From the cor. of Tps. 20 S., Rs. 9 and 10 W., East re-tracing the line bet. secs. 1 and 31, and at 20.63 chs. fall 29 lks. S. of the point for closing cor. of Tps. 21 S., Rs. 9 and 10 W. The course and length of this line is N.89°12'E., 20.63 chs.

I commence at the cor. of secs. 3, 4, 33 and 34, the point for which is located by reference to the old NE. and NW. bearing trees, which are dead and badly decayed. At the exact cor. point set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 33 and 34, with brass cap marked

T20S R10W	
S33	S34
S4	S3
T21S	
1919	

from which

A chittem, 12 ins. diam., bears N.22°E., 82 lks. dist., marked T 20 S R 10 W S 34 B T.

An alder, 24 ins. diam., bears S.64°E., 17 lks. dist., marked T 21 S R 10 W S 3 B T.

A chittem, 6 ins. diam., bears S.39°W., 47 lks. dist., marked T 21 S R 10 W S 4 B T.

A vine maple, 6 ins. diam., bears N.74°W., 39 lks. dist., marked T 20 S R 10 W S 33 B T.

Thence

N.87°44'E., resurveying the N. bdy. of Sec. 3.

Ascend SW. slope, through heavy timber and dense undergrowth, 290 ft. to

8.05 Top of ridge, bears NW. and SE.; descend NE. slope, 180 ft. to

14.50 Ravine, course NW.; ascend SW. slope 550 ft. to

27.25 Top of ridge, bears NW. and SE.; descend NE. slope 50 ft. to

31.85 Bottom of descent; ascend along N. slope 40 ft. to

33.35 Top of spur, slopes NE.; descend.

33.89 (40.00 chs. departure from cor. of secs. 2 and 3)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass