

County Surveyor's Record, Douglas County, Oregon

Resurvey Portion North Bdy., T. 21 S., R. 10 W.

CHAINS

cap marked

1/4 S3
1919

from which

A maple, 10 ins. diam., bears S.22°E., 20 lks. dist.,
marked 1/4 S 3 B.T.

A chitten, 8 ins. diam., bears S.56°W., 68 lks. dist.,
marked 1/4 S 3 B T.

Descend 160 ft. to

39.51 1/2 Apportioned distance.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for 1/4 sec. cor. of sec. 34 only, with brass cap
marked

1/4 S34
1919

from which

A chitten, 8 ins. diam., bears N.10°E., 61 lks. dist.,
marked 1/4 S 34 B T.

A fir, 14 ins. diam., bears N.6°W., 66 lks. dist.,
marked 1/4 S 34 B T.

Descend gradually.

- 40.95 Creek, 2 lks. wide, course N.; ascend W. slope 40 ft. to
- 42.05 Top of ridge, bears N. and S.; descend E. slope 260 ft. to
- 50.05 Dry bed of creek, course N.; ascend NW. slope 290 ft. to
- 55.45 Top of spur, slopes NE.; descend E. slope 180 ft. to
- 59.85 Dry ravine, course N.; ascend NW. slope 175 ft. to
- 65.15 Top of spur, slopes N.; thence along N. slope.
- 67.55 Top of spur, slopes NE.; descend gradual E. slope 220 ft.
to
- 73.91 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of secs. 2 and 3, with brass cap
marked

S3 | S2
T21S R10W
1919

from which