

Resurvey Portion North Bdy., T. 21 S., R. 10 W.

CHAINS

A fir, 40 ins. diam., bears S.25°E., 50 lks. dist.,  
marked T 21 S R 10 W S 2 B T.

A fir, 30 ins. diam., bears S.72°W., 33 lks. dist.,  
marked T 21 S R 10 W S 3 B T.

N.87°44'E., resurveying the N. bdy. of sec. 2.

Descend gradual E. slope, through heavy timber and dense undergrowth, 20 ft. to

5.12 Intersect the point for old cor. of secs. 2, 3, 34, and 35, located by reference to the SE. and NE. bearing trees, the NE. tree having fallen. I change this corner to refer to secs. 34 and 35 only and at the exact cor. point set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 34 and 35, with brass cap marked

T20S R10W  
S34 | S35

1919

from which

A fir, 6 ins. diam., bears N.25°E., 117 lks. dist.,  
marked T 20 S R 10 W S 35 B T.

A fir, 8 ins. diam., bears N.8°W., 184 lks. dist.,  
marked T 20 S R 10 W S 34 B T.

From this cor.

S.89°29'E., resurveying the N. bdy. of sec. 2.

Descend E. slope 130 ft. to

0.63 Stream, 10 lks. wide, course N.10°W.; ascend steep W. slope 590 ft. to cor.

10.50 Leave timber, bears N. and S.; enter fern opening and ascend gently rolling upland.

22.35 Enter scattering timber, bears N. and S.

24.27 Leave timber; enter fern opening, bears N. and S.

29.60 Enter timber, bears N. and S.

36.25 Intersect the point for  $\frac{1}{4}$  sec. cor., located by reference to the old SW. bearing tree. I obliterate marks on