

County Surveyor's Record, Douglas County, Oregon

Resurvey Portion North Bdy., T. 21 S., R. 10 W.

CHAINS

this tree and at the exact cor. point set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor. of sec. 35 only, with brass cap marked

1/4 S35  
-1919

from which

An alder, 10 ins. diam., bears N.62°E., 21 lks. dist., marked 1/4 S 35 B T.

A wild cherry, 10 ins. diam., bears N.9°W., 55 lks. dist., marked 1/4 S 35 B T.

From this cor.

N.87°28'E., resurveying the N. bdy. of sec. 2. Ascend gradually.

0.21 (40.00 chs. departure from the cor. of secs. 1 and 2)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor. of sec. 2 only, with brass cap marked

1/4 S2  
-1919

from which

A wild cherry, 12 ins. diam., bears S.14°E., 30 lks. dist., marked 1/4 S 2 B T.

A maple, 6 ins. diam., bears S.7°W., 10 lks. dist., marked 1/4 S 2 B T.

Ascend W. slope 90 ft. to

7.75 Top of spur ridge, bears N. and S., slopes S.; descend E. slope 430 ft. to

32.75 Foot of descent; ascend W. slope 115 ft. to

35.45 Top of spur, slopes SW.; thence along S. slope.

38.91 Intersect the old cor. of secs. 1, 2, 35, and 36, which is a decayed post, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 35 and 36 only and obliterate the marks on the old SE. and SW. bearing trees and alongside the old post set an iron post, 3 ft. long, 2 ins. diam.,