

Resurvey Portion North Bdy., T. 21 S., R. 10 W.

CHAINS

24 ins. in the ground, for cor. of secs. 35 and 36,
with brass cap marked .

T20S	R10W
S35	S36

1919

from which

A fir, 18 ins. diam., bears N.44°E., 36 lks. dist.,
marked T 20 S R 10 W S 36 B T (old B.T.)

A fir, 18 ins. diam., bears N.27½°W., 14 lks. dist.,
marked T 20 S R 10 W S 35 B T (Old B.T.)

From this cor.

S.89°58'E., resurveying the N. bdy. of Sec. 2.

Ascend gradually 15 ft. to

1.32 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 1 and 2, with brass cap marked

S2	S1
T21S	R10W

1919

from which

A hemlock, 10 ins. diam., bears S.53°E., 25 lks.
dist., marked T 21 S R 10 W S 1 B T.

A hemlock, 28 ins. diam., bears S.55°W., 22 lks.
dist., marked T 21 S R 10 W S 2 B T.

S.89°58'E., resurveying the N. bdy. of Sec. 1.

Along S. slope, through heavy timber and dense undergrowth.

10.00 Descend gradually on SE. slope 330 ft. to

33.00 Stream, 9 lks. wide, course N.80°E.; ascend steep NW.
slope 160 ft. to .

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for ¼ sec. cor. of sec. 1 only, with brass cap
marked

¼ S1

1919

from which

A fir, 48 ins. diam., bears S.73°E., 27 lks. dist.,
marked ¼ S 1 B T.