

260

County Surveyor's Record, Douglas County, Oregon

Resurvey Portion North Bdy., T. 21 S., R. 10 W.

CHAINS

A hemlock, 9 ins. diam., bears S.36°W., 44 lks.dist., marked 1/4 S 1 B T.

Descend NE. slope 16 ft. to

41.15 Intersect the old 1/2 sec. cor., which is a badly decayed post, marked and witnessed as described by the surveyor general. I obliterate marks on the bearing tree referring to Sec. 1 and change this cor. to refer to sec. 36 only and alongside the old cor. set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor. of sec. 36 only, with brass cap marked

1/4 S36
1919

from which

A wild cherry, 10 ins. diam., bears N.26°E., 38 lks. dist., marked 1/4 S 36 B T (New B.T.)

An alder, 12 ins. diam., bears N.30°W., 10 lks. dist., marked 1/4 S 36 B T (Old B.T.)

From this cor.

N.89°33'E., resurveying the N. bdy. of sec. 1.

Descend E. slope 40 ft. to

- 0.80 Ravine, course N.; ascend steep NW. slope 175 ft. to
- 8.55 Top of spur, slopes N.; descend NE. slope 40 ft. to
- 9.40 Ravine, stream, 1 lk. wide, course N.; ascend NW. slope 70 ft. to
- 11.20 Top of spur, slopes NE.; descend E. slope 20 ft. to
- 13.70 Shallow ravine, course N.10°E.; ascend 100 ft. to
- 15.80 Top of spur, slopes N.; descend NE. slope 120 ft. to
- 21.60 Stream, 1 lk. wide, course NW.; ascend W. slope 90 ft. to
- 23.65 Top of spur, slopes NW.; descend along N. slope 135 ft. to
- 26.80 Ravine, course N.; ascend NW. slope 60 ft. to
- 28.80 Top of spur, slopes N.; descend NE. slope 135 ft. to
- 36.40 Intersect point for cor. of Tps. 20 S., Rs. 9 and 10 W., located by reference to the old bearing trees, which are marked as described by the surveyor general. At the exact cor. point set an iron post, 3 ft. long, 3 ins.