

Resurvey Portion North Bdy., T. 21 S., R. 10 W.

CHAINS

diam., 24 ins. in the ground, for cor. of Tps. 20 S.,
Rs. 9 and 10 W., with brass cap marked

T20S	
R10W	R9W
S36	S31

1919

from which

A maple, 14 ins. diam., bears N.64°E., 74 lks. dist.,
marked T 20 S R 9 W S 31 B T (Old B. T.)

A fir, 24 ins. diam., bears N.32°W., 65 lks. dist.,
marked T 20 S R 10 W S 36 B T (Old B.T.)

From this cor.

N.89°12'E., resurveying the N. bdy. of Sec. 1.

Descend NE. slope 200 ft. to

7.30 Stream, 3 lks. wide, course N.; continue gradual descent
30 ft. to

17.20 Smith River, course N.70°W.; thence in river.

20.63 The point for closing cor. of Tps. 21 S., Rs. 9 and 10 W.,
in river.

Retracement Portion West Bdy., T. 20 S., R. 9 W.
by Fred Mensch, U. S. Cadastral Engineer, under Special
Instructions dated April 8, 1920. -Group 56-

From the cor. of secs. 7, 12, 13, and 18, on W. bdy. of
T. 20 S., R. 9 W.

North, retracing W. bdy. of the Tp., making diligent
search for traces of the old lines, setting temp. cors.
at intervals of 40.00 chs., finding no evidence of line
or cors. and topography does not agree with the field
notes.

126.21 A corner, ultimately accepted as the cor. of Tps. 19 and
20 S., R. 10 W. bears West, 22.90 chs. dist.

134.08 The closing cor. of Tps. 19 and 20 S., R. 9 W. bears West,
22.83 chs. dist.

162.01 The $\frac{1}{4}$ sec. cor. on E. bdy. of sec. 36, T. 19 S., R. 10 W.
bears West, 22.58 chs. dist.

168.80 Set temp. Tp. cor.
