

County Surveyor's Record, Douglas County, Oregon

Resurvey of Portion East Bdy., T. 20 S., R. 10 W.

CHAINS
14.81

Point at 40.00 chs. northing from closing cor. of secs. 6 and 7, T. 20 S., R. 9 W.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap marked

|
 $\frac{1}{4}$
S 6
1921

from which

A cedar, 5 ins. diam., bears N.10°E., 8 lks. dist., marked $\frac{1}{4}$ S 6 B T.

A fir, 24 ins. diam., bears S.44°E., 41 lks. dist., marked $\frac{1}{4}$ S 6 B T.

Ascend 55 ft. on NW. slope.

16.65 Spur, slopes W.; descend 215 ft. on SW. slope.

25.00 Ravine, course W.; ascend 140 ft. on NW. slope.

30.50 Spur, slopes W.; descend 190 ft. on SW. slope.

36.15 Creek, 1 lk. wide, course W.; ascend 45 ft. on N. slope to

37.09 (Apportioned distance) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap marked

|
 $\frac{1}{4}$
S 1
1921

from which

A fir, 30 ins. diam., bears S.68°W., 25 lks. dist., marked $\frac{1}{4}$ S 1 B T.

A chittem, 6 ins. diam., bears N.89°W., 34 lks. dist., marked $\frac{1}{4}$ S 1 B T.

Ascend 130 ft. on NW. slope.

43.00 Ridge, bears NE. and SW.; descend 150 ft. on S. slope.

46.00 Ravine, course SW.; ascend 100 ft. on NW. slope.

50.00 Spur, slopes SW.; descend 200 ft. on S. slope to

55.46 Point of intersection with line bet. secs. 6 and 7, T. 20 S., R. 9 W., determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for closing cor. of secs. 6 and 7, with