

Resurvey of Portion East Bdy., T. 20 S., R. 10 W.

CHAINS

brass cap marked

	T20S	
T20S	S6	
R10W	S7	CC
S1	R9W	
	1921	

from which

A cedar, 30 ins. diam., bears N.37°E., 54 lks. dist.,  
marked T 20 S R 9 W S 6 C C B T.

An alder, 7 ins. diam., bears S.45°E., 9 lks. dist.,  
marked T 20 S R 9 W S 7 C C B T.

56.00 Creek, 2 lks. wide, course SW.; ascend 240 ft. on NW.  
slope.

61.25 Ridge, bears E. and W.; descend 160 ft. on S. slope.

65.20 Ravine, course SW.; ascend 50 ft. on NW. slope, to

67.49 Apportioned distance.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in  
the ground, for cor. of secs. 1 and 12, with brass cap  
marked

T20S	T20S
S1	
S12	R9W
R10W	S7
	1921

from which

A fir, 30 ins. diam., bears S.31°W., 42 lks. dist.,  
marked T 20 S R 10 W S 12 B T.

A cedar, 24 ins. diam., bears N.65°W., 11 lks. dist.,  
marked T 20 S R 10 W S 1 B T.

S.10°17'E., resurveying E. bdy. of sec. 12.

Over mountainous land, through heavy timber and dense  
undergrowth.

Ascend 150 ft. on NW. slope.

3.00 Spur, slopes SW.; ascend 120 ft. on broken W. slope.

26.50 Top of small peak, intersection of ridge, bears NE. and  
SW., and spur, slopes SE.; descend 75 ft. on S. slope to

28.62 Point at 40.00 chs. southing from closing cor. of secs.