

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 19 S., R. 10 W.

CHAINS	
	. summit of ridge, course SW.; ascend 200 ft. to
72.00	Top of spur, bears E.; descend 50 ft. to
80.00	The cor. of secs. 25 and 36, established on former survey,
	. which is a fir, 12 ins. diam., marked T 19 S 36 on SW.
	and R 10 W S 25 on NW. sides, with 1 groove on S. & 5
	grooves on N. sides; from which
	. A fir, 18 ins. diam., bears S.83°W., 71 lks. dist.,
	marked T 19 S R 10 W S 36 B T.
	. A fir, 18 ins. diam., bears N.3½°W., 6 lks. dist.,
	marked T 19 S R 10 W S 25 B T.
	North on E. bdy. of Sec. 25.
	Descend through burnt timber.
9.14	The old closing cor. to secs. 30 & 31, T. 19 S., R. 10 W.,
	which I destroy.
13.10	North Fork of Smith River, 60 lks. wide, 200 ft. below
	sec. cor., course SE.; ascend 150 ft. to
	Top of spur, brs. SW.; descend.
36.25	
40.00	Set a basalt stone, 12x10x8 ins., 9 ins. in the ground,
	for ¼ sec. cor., marked ¼ on W. face; from which
	. An alder, 4 ins. diam., bears N.10°W., 12 lks. dist.,
	. marked ¼ S 25 B T.
	. An alder, 4 ins. diam., bears S.19°W., 5 lks. dist.,
	marked ¼ S 25 B T.
	From this cor. the old ¼ sec. cor. brs. E, 4 lks. dist.;
	I destroy it.
73.10	North Fork of Smith River, 50 lks. wide, 150 ft. below
	Top of spur, course SW.; ascend 100 ft. to
80.00	The cor. of secs. 24 & 25, established on former survey,
	which is a post, 3 ft. long, 4 in. sq., 24 ins. in the
	ground, marked T 19 S S 25 on SW. and R 10 W S 24 on
	NW. faces, with 2 notches on S. & 4 notches on N. edges;
	from which
	. An alder, 8 ins. diam., bears S.25°W., 16 lks. dist.,
	marked T 19 S R 10 W S 25 B T.