

East Bdy. of T. 19 S., R. 10 W.

CHAINS

An alder, 7 ins. diam., bears N.34°W., 20 lks. dist.,  
marked T 19 S R 10 W S 24 B T.

July 5, 1899.

July 6, 1899.

North on the E. bdy. of Sec. 24.

Ascend through burnt timber & dense undergrowth.

9.22 The old closing cor. of secs. 19 & 30, T. 19 S., R. 9 W.;  
I destroy this cor.

16.00 Top of spur, 250 ft. above sec. cor., brs. SW.; descend  
140 ft. to

34.75 Creek, 2 lks. wide, flows SE.; ascend.

40.00 Set an alder post, 3 ft. long, 4 ins. sq., 24 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 24 on W. face; from  
which

An alder, 4 ins. diam., bears N.18°W., 15 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

An alder, 7 ins. diam., bears S.19°W., 17 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

From this cor. the old  $\frac{1}{4}$  sec. cor. brs. E. 4 lks. dist.;  
I destroy it.

55.60 Top of spur, 150 ft. above creek, brs. SE.; descend 100 ft.  
to

62.25 Creek, 2 lks. wide, course SE.; ascend 200 ft. to

80.00 Set an alder post, 3 ft. long, 4 ins. sq., 24 ins. in the  
ground, for the cor. of secs. 13 & 24, marked T 19 S S  
24 on SW. and R 10 W S 13 on NW. faces, with 3 notches  
on N. & S. edges; from which

An alder, 8 ins. diam., bears N.25°W., 12 lks. dist.,  
marked T 19 S R 10 W S 13 B T.

An alder, 4 ins. diam., bears S.80°W., 27 lks. dist.,  
marked T 19 S R 10 W S 24 B T.

From this cor. the old cor. brs. E. 9 lks. dist.; I de-  
stroy it.