

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 19 S., R. 10 W.

CHAINS

North on E. bdy. of Sec. 13.

Ascend through burnt timber and dense undergrowth.

9.30 The old closing cor. of secs. 18 & 19, T. 19 S., R. 10 W.;

I destroy it.

31.50 Top of spur, 300 ft. above sec. cor., brs. SE.; descend.

40.00 Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 13 on W. face; from which

A fir, 8 ins. diam., brs. N.9°W., 10 lks. dist., marked $\frac{1}{4}$ S B T.

A fir, 6 ins. diam., brs. S.70°W., 19 lks. dist., marked $\frac{1}{4}$ S B T.

The old $\frac{1}{4}$ sec. cor. brs. S.87°E., 5 lks. dist.; I destroy it.

55.80 Spring branch, 1 lk. wide, 100 ft. below top of spur, course E.; ascend.

67.00 Top of ridge, 150 ft. above creek, brs. East; descend 200 ft. to

80.00 Set a sandstone, 20x6x5 ins., 15 ins. in the ground, for cor. of secs. 12 & 13, marked with 4 notches on S. & 2 notches on N. edges; from which

An alder, 4 ins. diam., bears N.5°W., 28 lks. dist., marked T 19 S R 10 W S 12 B T.

A fir, 6 ins. diam., bears S.63°W., 73 lks. dist., marked T 19 S R 10 W S 13 B T.

From this cor. old cor. brs. S.80°W., 15 lks. dist.; I destroy it.

July 6, 1899.

North on E. bdy. of Sec. 12.

Descend through burnt timber and dense undergrowth.

4.00 Enter green timber, brs. E. & W.

4.75 Ravine, 50 ft. deep, course E.; ascend 60 ft. to

9.00 Top of spur, bears E.; descend.

9.45 The old closing cor. of secs. 7 and 18; I destroy it.