

East Bdy. of T. 19 S., R. 10 W.

- CHAINS
11.50 Ravine, 50 ft. deep, course SE.; ascend 150 ft. to
17.25 Top of spur, brs. SE.; descend along E. slope, over spurs
and ravines.
40.00 Set a sandstone, 12x8x7 ins., 8 ins. in the ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which
A hemlock, 5 ins. diam., bears S.58°W., 14 lks. dist.,
marked $\frac{1}{4}$ S 12 B T.
A hemlock, 6 ins. diam., bears N.48°W., 19 lks. dist.,
marked $\frac{1}{4}$ S 12 B T.
The old $\frac{1}{4}$ sec. cor. bears S.1°E., 20 lks. dist.; I destroy
it.
47.75 Ravine, 300 ft. below sec. cor., course SE.; ascend along
E. slope over ravines and spurs.
50.00 Enter burn, bears E. and W.
72.50 The old closing cor. of secs. 6 & 7, T. 19 S., R. 9 W.;
I also destroy it and at
79.60 Intersect the old cor. of secs. 1 and 12, which I destroy.
80.00 Set a sandstone, 12x10x6 ins., 8 ins. in the ground, for
cor. of secs. 1 and 12, marked 5 notches on S. and 1
notch on N. edges; from which
A dead fir, 7 ins. diam., bears N.16°W., 50 lks. dist.,
marked T 19 S R 10 W S 1 B T.
A dead fir, 14 ins. diam., bears S.40°W., 74 lks.
dist., marked T 19 S R 10 W S 12 B T.

Subdivisions of T. 19 S., R. 10 W., W. M.
Survey by Henry L. Chandler under Contract No. 705 dated
April 14th, 1899.

Survey commenced July 15, 1899, at the SE. cor. T. 19 S.,
R. 10 W., which is a post, marked and witnessed as de-
scribed by the surveyor general; thence I run
S.89°49'W., retracing the S. bdy. of Sec. 36, and at
39.97 chs. fall 2 lks. S. of the $\frac{1}{4}$ sec. cor., and at
80.00 chs. intersect the cor. of secs. 1, 2, 35, and
36, on S. bdy. of Tp.

The bearing of this line is as stated by the surveyor