

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 10 W.

CHAINS

general and my chaining practically agrees with the original survey.

I begin at the cor. of secs. 1, 2, 35, & 36, on S. bdy. of Tp., which is a post, marked and witnessed as described by the surveyor general.

Thence I run

N.0°01'W., bet. secs. 35 and 36.

Ascend through young fir timber and dense undergrowth.

13.75 Top of spur, 200 ft. above sec. cor., bears SW.; descend 75 ft. to

17.00 Ravine, course SW.; ascend 50 ft. to

18.60 Top of spur, bears SW.; descend 75 ft. to

23.50 Ravine, course SW.; ascend 80 ft. to

26.20 Top of spur, bears SW.; descend 250 ft. to

40.00 The $\frac{1}{2}$ sec. cor., established on former survey, which is a chitten tree, 6 ins. diam., marked $\frac{1}{2}$ S 35 on W. & 36 on E. sides; from which

A vine maple, 6 ins. diam., bears S.25°E., 16 lks. dist., marked $\frac{1}{2}$ S B T.

A fir, 10 ins. diam., bears S.83°W., 16 lks. dist., marked $\frac{1}{2}$ S B T.

This cor. is in the S. edge of a vine maple bottom, bears E. & W.

59.75 Leave bottom, bears E. & W.; ascend 100 ft. to

75.00 Top of spur, bears W.; descend 60 ft. to

80.00 The cor. of secs. 25, 26, 35, and 36, established on former survey, which is a fir post, 3 ft. long, 4 ins. sq., set 24 ins. in the ground, marked T 19 S S 25 on NE., R 10 W S 36 on SE., S 35 on SW. and S 26 on NW. faces, with 1 notch on the S. & E. edges; from which

An alder, 5 ins. diam., bears N.77°E., 19 lks. dist., marked T 19 S R 10 W S 25 B T.

A hemlock, 6 ins. diam., bears S.5°E., 23 lks. dist., marked T 19 S R 10 W S 36 B T.

A vine maple, 6 ins. diam., bears S.43°W., 8 lks.