

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 10 W.

CHAINS 34.25	Top of spur, 150 ft. above river, brs. NE.; descend.
40.00	Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 26 on W. and 25 on E. faces; from which <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S.10°E., 8 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S.19°W., 14 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p> <p style="margin-left: 40px;">The old <math>\frac{1}{4}</math> sec. cor. bears S.80°E., 3 lks. dist.; I destroy it.</p>
56.85	Ravine, 150 ft. below spur, course NE.; ascend 150 ft. to
67.00	Summit of ridge, bears E. & W.; descend 100 ft. to
80.00	The cor. of secs. 23, 24, 25, and 26, established on former survey, which is a chittem post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, marked T 19 S S 24 on NE., R 10 W S 25 on SE., S 26 on SW. and S 23 on NW. faces, with 2 notches on S. and 1 notch on E. edges; from which <p style="margin-left: 40px;">A chittem, 5 ins. diam., bears N.11°E., 26 lks. dist., marked T 19 S R 10 W S 24 B T.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S.17°E., 20 lks. dist., marked T 19 S R 10 W S 25 B T.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S.30°W., 17 lks. dist., marked T 19 S R 10 W S 26 B T.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears N.70°W., 40 lks. dist., marked T 19 S R 10 W S 23 B T.</p>
	N.89°58'E., on a random line, bet. secs. 24 and 25.
40.00	Set temporary $\frac{1}{4}$ sec. cor.
80.04	Intersect the E. bdy. of Tp., 14 lks. S. of the cor. of secs. 24 and 25.  Thence I run S.89°52'W., bet. secs. 24 and 25.  Ascend through burnt timber and dense undergrowth.
21.00	Top of spur, 200 ft. above sec. cor., bears SE.; descend