

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 10 W.

CHAINS

A fir, 8 ins. diam., bears S.12½°E., 31 lks. dist.,
marked T 19 S R 10 W S 24 B T.

A fir, 6 ins. diam., bears S.36°W., 11 lks. dist.,
marked T 19 S R 10 W S 23 B T.

A fir, 5 ins. diam., bears N.9°W., 10 lks. dist.,
marked T 19 S R 10 W S 14 B T.

July 16, 1899.

N.89°52'E., on a random line, bet. secs. 13 and 24.

40.00 Set temporary ¼ sec. cor.

79.98 Intersect the E. bdy. of T., 19 lks. N. of the cor. of
secs. 13 and 24.

Thence I run

West, on a true line, bet. secs. 13 and 24.

Ascend through burnt timber and dense undergrowth.

9.00 Top of spur, 100 ft. above sec. cor., bears SE.; descend
150 ft. to

17.70 Ravine, course SE.; ascend 150 ft. to

37.50 Top of spur, bears S.; descend.

39.99 Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground,
for ¼ sec. cor., marked ¼ S 13 on N. and 24 on S. faces;
from which

A fir, 6 ins. diam., bears N.30°E., 10 lks. dist.,
marked ¼ S B T.

A fir, 4 ins. diam., bears S.25°W., 12 lks. dist.,
marked ¼ S B T.

The old ¼ sec. cor. bears S., 7 lks. dist.; I destroy it.

57.00 Ravine, 100 ft. below spur, course S.; ascend 100 ft. to

72.10 Top of spur, bears SE.; descend 75 ft. to

79.98 The cor. of secs. 13, 14, 23, and 24.

N.0°1'W., bet. secs. 13 and 14.

Ascend through burnt timber and dense undergrowth.

15.00 Top of spur, 150 ft. above sec. cor., bears SE.; descend