

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 10 W.

CHAINS

N.0°02'W., bet. secs. 26 & 27.

Over nearly level land, through burnt timber & dense undergrowth.

13.10 Trail, bears E. & W.

15.60 North Fork of Smith River, 70 lks. wide, course W.

16.60 Rocky bluff, 60 ft. high; thence ascend gradually.

40.00 The $\frac{1}{4}$ sec. cor. established on former survey, which is a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, marked $\frac{1}{4}$ S 27 on W. & 26 on E. faces; from whichA fir, 7 ins. diam., bears N.20°E., 10 lks. dist., marked $\frac{1}{4}$ S B T.A fir, 4 ins. diam., bears S.16°W., 9 lks. dist., marked $\frac{1}{4}$ S B T.

43.25 Summit of ridge, 250 ft. above river, bears E. & W.; descend 150 ft. to

61.00 Ravine, course SW.; ascend 150 ft. to

80.00 Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 22, 23, 26 & 27, marked T 19 S S 23 on NE., R 10 W S 26 on SE., S 27 on SW. and S 22 on NW. faces, with 2 notches on S. & E. edges; from which

A fir, 4 ins. diam., bears N.10°E., 15 lks. dist., marked T 19 S R 10 W S 23 B T.

A fir, 4 ins. diam., bears S.25°E., 10 lks. dist., marked T 19 S R 10 W S 26 B T.

A fir, 5 ins. diam., bears S.50°W., 26 lks. dist., marked T 19 S R 10 W S 27 B T.

A fir, 6 ins. diam., bears N.8°W., 20 lks. dist., marked T 19 S R 10 W S 22 B T.

The old cor. bears East, 7 lks. dist.; I destroy it.

July 20, 1899.

N.89°55'E., on a random line, bet. secs. 23 & 26.

40.00 Set a temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. & S. line, 9 lks. N. of the cor. of secs.