

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 10 W.

CHAINS

150 ft. to

76.10 Ravine, course SE.; ascend 75 ft. to

80.00 Set an alder post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 14, 15, 22 & 23, marked T 19 S S 14 on NE., R 10 W S 23 on SE., S 22 on SW. and S 15 on NW. faces, with 3 notches on S. & 2 notches on E. edges; from which

An alder, 4 ins. diam., bears N.20°E., 15 lks. dist., marked T 19 S R 10 W S 14 B T.

An alder, 5 ins. diam., bears S.35°E., 30 lks. dist., marked T 19 S R 10 W S 23 B T.

A fir, 6 ins. diam., bears S.38°W., 17 lks. dist., marked T 19 S R 10 W S 22 B T.

A fir, 4 ins. diam., bears N.50°W., 32 lks. dist., marked T 19 S R 10 W S 15 B T.

The old cor. bears S.80°W., 7 lks. dist.; I destroy it.

N.89°59'E., on a random line, bet. secs. 14 & 23.

40.00 Set a temp. $\frac{1}{4}$ sec. cor.

79.88 Intersect N. & S. line, 6 lks. N. of the cor. of secs. 13, 14, 23, and 24.

Thence I run

N.89°58'W., on true line, bet. secs. 14 & 23.

Descend through burnt timber & dense undergrowth.

6.00 Ravine, 75 ft. below sec. cor.; course SE.; ascend 175 ft. to

23.50 Top of spur, bears SE.; descend 150 ft. to

30.00 Ravine, course SE.; ascend.

39.94 The $\frac{1}{4}$ sec. cor. established on former survey, which is a fir post, 3 ft. long, 3 ins. sq., set 24 ins. in the ground, marked $\frac{1}{4}$ S 14 on N. & 23 on S. faces; from which

A fir, 6 ins. diam., bears N.9°W., 13 lks. dist., marked $\frac{1}{4}$ S B T.