

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 10 W.

CHAINS

A hemlock, 6 ins. diam., bears S.83°W., 40 lks. dist.,
marked T 19 S R 10 W S 15 B T.

An alder, 10 ins. diam., bears N.52°W., 56 lks. dist.,
marked T 19 S R 10 W S 10 B T.

The old cor. bears S.20°W., 1.00 ch. dist.; I destroy it.

S.89°58'E., on a random line, bet. secs. 11 and 14.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. & S. line, 10 lks. N. of cor. of secs. 11,
12, 13, & 14.

Thence I run

N.89°54'W., on true line, bet. secs. 11 & 14.

Ascend through burnt timber and dense undergrowth.

7.00 Top of spur, 75 ft. above sec. cor., bears NW.; descend
150 ft. to

24.00 Ravine, course NW.; ascend 100 ft. to

37.50 Top of spur, bears NW.; descend.

40.00 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 11 on N. and 14 on
S. faces; from which

A fir, 6 ins. diam., bears N.70°E., 31 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 4 ins. diam., bears S.12°W., 10 lks. dist.,
marked $\frac{1}{4}$ S B T.

Old $\frac{1}{4}$ sec. cor. bears S.29°W., 60 lks. dist.; I destroy
it.

56.10 Ravine, 100 ft. below spur, course NW.; ascend 150 ft. to

68.00 Top of spur, bears NW.; descend 150 ft. to

74.50 Creek, 3 lks. wide, course NW.; ascend 100 ft. to

80.00 The cor. of secs. 10, 11, 14 & 15.

From the cor. of secs. 3, 4, 33 & 34, on S. bdy. of Tp.,
which is a post, marked and witnessed as described by
the surveyor general; thence I run

N.0°02'W., bet. secs. 33 & 34.