

Subdivisions of T. 19 S., R. 10 W.

CHAINS  
 40.05 Ravine, course NW.; ascend 200 ft. to  
 68.00 Top of spur, bears NE.; descend 150 ft. to  
 80.00 Set a sandstone, 12x8x7 ins., 8 ins. in the ground, for  
 cor. of secs. 21, 22, 27 & 28, marked with 2 notches on  
 S. and 3 notches on E. edges; and raised a mound of  
 stone, 2 ft. base, 1½ ft. high, W. of cor. Pits im-  
 practicable. No tree within limits.  
 Old cor. bears W. 5 lks. dist.; I destroy it.  
 July 25, 1899.

N.89°44'E., on a random line, bet. secs. 22 and 27.  
 40.00 Set a temp. ¼ sec. cor.  
 79.86 Intersect N. and S. line, 28 lks. N. of the cor. of secs.  
 22, 23, 26 & 27.  
 Thence I run  
 S.89°56'W., on a true line, bet. secs. 22 and 27.  
 Ascend through burnt timber & brush.  
 13.00 Top of spur, 125 ft. above sec. cor.; descend 150 ft. to  
 33.15 Ravine, course SW.; ascend.  
 39.93 The old ¼ sec. cor. established on former survey, which  
 is a post, 3 ft. long, 3 ins. sq., set 24 ins. in the  
 ground, marked ¼ S 22 on N. and 27 on S. faces; from  
 which  
 A fir, 6 ins. diam., bears N.15°E., 12 lks. dist.,  
 marked ¼ S B T.  
 A fir, 7 ins. diam., bears S.20°W., 11 lks. dist.,  
 marked ¼ S B T.  
 48.00 Top of spur, 150 ft. above ravine, bears SE.; descend 100  
 ft. to  
 65.05 Spring branch, 1 lk. wide, course S.; ascend 100 ft. to  
 79.86 The cor. of secs. 21, 22, 27 & 28.

N.0°02'W., bet. secs. 21 and 22.  
 Descend through burnt timber and dense undergrowth.