

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 10 W.

CHAINS

An alder, 6 ins. diam., bears N.65°W., 18 lks. dist., marked 1/4 S B T.

An alder, 4 ins. diam., bears S.20°E., 10 lks. dist., marked 1/4 S B T.

Old cor. bears S.85°W., 9 lks. dist.; I destroy it.

56.75 Ravine, 150 ft. below top of spur, course NW.; ascend 200 ft. to

74.50 Summit of ridge, bears E. & W.; descend 40 ft. to

80.00 Set a sandstone, 12x8x7 ins., 8 ins. in the ground, for cor. of secs. 16, 17, 20 & 21, marked with 3 notches on S. and 4 notches on E. edges; and raised a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. Pits impracticable; no trees within limits.

Old cor. bears E. 8 lks. dist.; I destroy it.

N.89°50'E., on a random line, bet. secs. 16 and 21.

40.00 Set a temp. 1/4 sec. cor.

79.82 Intersect N. & S. line, 14 lks. S. of the cor. of secs. 15, 16, 20 & 21.

Thence I run

S.89°44'W., on a true line, bet. secs. 16 and 21.

Descend through burnt timber and dense undergrowth.

11.65 Ravine, 100 ft. below sec. cor., course N.; ascend 200 ft. to

29.75 Summit of ridge, bears N. & S.; descend.

39.91 Set a sandstone, 16x6x6 ins., 12 ins. in the ground, for 1/2 sec. cor., marked 1/4 on N. face; and raised a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor. Pits impracticable; no trees in limits.

The old 1/4 sec. cor. bears S.80°W., 12 lks. dist.; I destroy it.

43.20 Ravine, 150 ft. below ridge, course NW.; ascend 150 ft. to

72.00 Top of spur, bears NE.; descend 30 ft. to

79.82 The cor. of secs. 16, 17, 20 and 21.

July 31, 1899.