

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 10 W.

CHAINS	
40.00	Set a temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. & S. line, 32 lks. N. of the cor. of secs. 28, 29, 32 & 33. Thence I run N.89°57'W., on a true line, bet. secs. 29 & 32. Descend through burnt timber and dense undergrowth.
10.00	N. Fork of Smith River, 100 lks. wide, 150 ft. below sec. cor., course S.; ascend 200 ft. to
28.00	Top of spur, bears SW.; descend 125 ft. to
35.45	Spring branch, 1 lk. wide, course SW.; ascend.
40.00	The $\frac{1}{4}$ sec. cor. established on former survey, which is a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, marked $\frac{1}{4}$ S 29. on N. & 32 on S. faces; from which. An alder, 5 ins. diam., bears S.12°E., 16 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 10 ins. diam., bears N.60°E., 69 lks. dist., marked $\frac{1}{4}$ S B T.
63.25	Summit of divide bet. N. Fork of Smith River & Fiddle Creek, 300 ft. above spring branch, bears NE. & SW.; descend 100 ft. to
80.00	The cor. of secs. 29, 30, 31, & 32. N.0°04'W., bet. secs. 29 & 30. Descend through burnt timber and dense undergrowth.
19.10	Ravine, 100 ft. below sec. cor., course SW.; ascend.
40.00	Set a basalt stone, 12x8x7 ins., 8 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raised a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. No trees within limits. Old cor. bears E., 15 lks. dist.; I destroy it.
46.75	Top of spur, 150 ft. above ravine, bears NW.; descend 100 ft. to
64.25	Ravine, course W.; ascend 150 ft. to
80.00	The cor. of secs. 19, 20, 29 & 30, established on former