

Subdivisions of T. 19 S., R. 10 W.

CHAINS

survey, which is a post, 3 ft. long, 4 ins. sq., set 24 ins. in the ground, marked T 19 S S 20 on NE., R 10 W S 29 on SE., S 30 on SW. and S 19 on NW. faces, with 2 notches on S. and 5 notches on E. edges; from which

A fir, 6 ins. diam., bears N.80°E., 10 lks. dist., marked T 19 S R 10 W S 20 B T.

A fir, 8 ins. diam., bears S.6°E., 50 lks. dist., marked T 19 S R 10 W S 29 B T.

A fir, 7 ins. diam., bears S.70½°W., 67 lks. dist., marked T 19 S R 10 W S 30 B T.

A fir, 6 ins. diam., bears N.14°W., 30 lks. dist., marked T 19 S R 10 W S 19 B T.

S.89°57'E., on a random line, bet. secs. 20 & 29.

40.00 Set a temp. ¼ sec. cor.

79.76 Intersect N. & S. line, 5 lks. S. of the cor. of secs. 20, 21, 28 & 29.

Thence I run

N.89°59'W., on a true line, bet. secs. 20 & 29.

Descend through burnt timber and dense undergrowth.

32.90 Ravine, 200 ft. below sec. cor., course SW.; ascend.

39.88 Set an alder post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for ¼ sec. cor., marked ¼ S 20 on N. and 29 on S. faces; from which

An alder, 4 ins. diam., bears N.8°E., 12 lks. dist., marked ¼ S B T.

An alder, 4 ins. diam., bears S.50°E., 40 lks. dist., marked ¼ S B T.

Old cor. bears N.82°E., 12 lks. dist.; I destroy it.

56.50 Top of spur, 250 ft. above ravine, bears SW.; descend 150 ft. to

79.76 The cor. of secs. 19, 20, 29 & 30.