

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 9 W.

CHAINS

A fir, 60 in. in dia., bears S.27°W., 80 lks. dist.  
 A fir, 50 in. in dia., bears S.71 $\frac{1}{4}$ °E., 41 lks. dist.  
 A maple, 36 in. in dia., bears N.66 $\frac{1}{2}$ °W., 1.01 chs. dist.  
 An alder, 18 in. in dia., bears N.18 $\frac{3}{4}$ °E., 1.20 chs. dist.

East, on true line, of south boundary of Sec. 32.

Var.19 $\frac{1}{2}$ °East.

- 1.55 Buck Creek, 20 lks. wide, c N.; commence ascent. -50
- 17.00 Top of ridge, bears N. and S.; commence steep descent. +400
- 22.50 Marshy flat. -120
- 40.00 Set a chitten post for  $\frac{1}{4}$  sec. cor. bet. secs. 32 and 5;  
 from which  
     A maple, 24 in. in dia., bears S.62 $\frac{1}{2}$ °E., 88 lks. dist.  
     A fir, 36 in. in dia., bears N.64°E., 55 lks. dist.  
 Commence ascent.
- June 7th.
- 44.00 Top of rise; commence descending. +40
- 53.00 Buck Creek, 10 lks. wide, c S. -30
- 54.00 Same creek; commence ascent.
- 71.25 Top of spur. +300
- 80.00 Near head of canyon. Set a rock, 30x16x16, with 3  
 smaller ones piled around, for cor. to secs. 32, 33, 4  
 and 5; from which  
     A fir, 40 in. in dia., bears S.33 $\frac{1}{2}$ °E., 1.16 chs. dist.  
     A fir, 36 in. in dia., bears S.33 $\frac{1}{2}$ °W., 1.86 chs. dist.  
     A cedar, 30 in. in dia., bears N.49 $\frac{3}{4}$ °W., 1.22 chs. dist.  
     A fir, 36 in. in dia., bears N.29 $\frac{1}{2}$ °E., 33 lks. dist.

East, on true line, of south boundary of Sec. 33.

Var.19°35' East.

- 4.41 Top of spur, bears NE. and SW. +100