

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.
 Survey by Wm. Thiel under Contract 260 dated Apr. 17, 1877.

CHAINS		
	Begin at post to sections 33, 34, 3 & 4, T. 20 & 21 S., R. 9 W., as just established by me, running thence North between sections 33 and 34.	
	Var. 19°35' East.	
2.00	Branch, 3 lks. wide, c W.	
2.40	Commence ascent.	
17.00	Gulch, c E.	
24.60	Perpendicular cliff, 50 ft. high.	
25.50	Top of spur, c W. and E.	+450
29.50	Gulch, c W.	-60
32.00	Top of spur, c W. and E.; commence descent.	+70
40.00	Set $\frac{1}{2}$ sec. post; from which A cedar, 42 in. in dia., bears N.60°E., 5 lks. dist. A cedar, 24 in. in dia., bears N.80 $\frac{1}{2}$ °W., 1.00 ch. distant.	-80
42.50	Gulch, c W.; commence ascent.	-20
	June 8th.	
53.50	Top of rise on a spur.	+250
57.40	Top of main ridge, giving a good view; commence descending SE. slope.	+50
71.00	Bluff, 20 ft. high.	
80.00	Set post to secs. 27, 28, 33 and 34 on SE. slope; from which A fir, 24 in. in dia., bears N.62 $\frac{1}{2}$ °E., 48 lks. dist. A fir, 36 in. in dia., bears S.34 $\frac{1}{2}$ °E., 3.42 chs. dist. A fir, 10 in. in dia., bears S.40 $\frac{1}{2}$ °W., 48 lks. dist. A fir, 30 in. in dia., bears N.17 $\frac{3}{4}$ °W., 49 lks. dist.	-200
	East, on a true line, between secs. 27 and 34. Va. 19°35' East.	
11.75	Smiths River, c NNE., 1.50 chs. wide, and 2 $\frac{1}{2}$ ft. deep, rapids about 5.00 chs. above.	
13.25	Enter narrow bottom.	