

Subdivisions of T. 20 S., R. 9 W.

CHAINS		
	On account of deep canyon in front, sight line N. to a fir, the only green one on opposite ridge; then lay off base W. 100 lks.; flag tree bears thence N.3°22'E, making 17.09 chs. across.	
31.54	Top of main divide, c NW. and SE.; commence descent on steep E. hill slope.	+250
40.00	Set $\frac{1}{4}$ sec. post; from which A cedar, 36 in. in dia., bears S.21 $\frac{1}{2}$ °W., 47 lks. dist. A cedar, 32 in. in dia., bears N.49 $\frac{1}{4}$ °E., 1.23 chs. dist.	-100
42.55	Gulch, c E.	-60
52.00	Top of spur, c N.30°E. and S.30°W.	+75
58.80	Gulch, c N.60°W. and S.60°E.	-90
62.50	Top of spur, c S.30°W. and N.30°E.; commence descending.	+40
70.00	A cedar, 14 in. in dia.	
73.00	Left river bank, course N.10°W.; thence by traverse N.17 $\frac{1}{2}$ ° E., 2.50 chs.; cross on rapids N.22 $\frac{3}{4}$ °W., 1.87 chs., making due N. 4.11 chs. to line.	
77.11	Alder, 16 in. in dia.	
78.50	Clearing.	
80.00	Set post to sections 28, 29, 32 and 33; from which A cedar, 42 ins. dia., bears S.51 $\frac{3}{4}$ °E., 51 lks. dist. A fir, 42 in. in dia., bears N.25 $\frac{3}{4}$ °E., 1.26 chs. dist. An alder, 30 in. in dia., bears N.17 $\frac{1}{2}$ °W., 68 lks. dist. A maple, 12 in. in dia., bears S.85 $\frac{1}{2}$ °W., 94 lks. dist. June the 12th.	
S.89°21'W., on true line, bet. secs. 28 and 33. Var.19°35'East.		
2.50	Top of ridge, c N. & S.	+60
6.00	Top of rocky spur, c NW.; commence descending.	-500
27.00	Bottom.	-500
30.10	Bank of river, course S.10°E., 2.10 chs. wide.	
32.25	Commence steep ascent.	