

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20. S., R. 8 W.

CHAINS

marked T 20 S R 8 W S 7 B T.

Dogwood, 6 in. dia., bears S.63°E., 30 lks. dist.,

marked T 20 S R 8 W S 18 B T.

Hemlock, 8 in. in dia., bears S.46°W., 5 lks. dist.,

marked T 20 S R 9 W S 13 B T.

Maple, 20 in. in dia., bears N.65°W., 36 lks. dist.,

marked T 20 S R 9 W S 12 B T.

North between secs. 7 & 12.

V.20°E.

Ascend.

- 6.50 Top of hill; descend.
- 15.00 Branch, 2 lks. wide, flows East.; ascend.
- 34.00 Cross ridge, course E. & W.; descend.
- 40.00 Set post, 4 in. dia., 4 ft. long, with marked stone, 12 in. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- Maple, 20 in. dia., bears N.40°W., 20 lks. dist.,
marked $\frac{1}{4}$ S B T.
- Maple, 20 in. dia., bears N.72°E., 36 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 42.50 Branch, 2 lks. wide, flows East; ascend.
- 57.50 On top of hill; descend.
- 69.00 Ascend.
- 80.00 Set post, 6 in. dia., 4 ft. long, in ground 12 in., with marked stone, for cor. to secs. 6, 7, 1 & 12, marked T 20 S S 6 on NE., R 8 W S 7 on SE., R 9 W S 12 on SW. S 1 on NW. face, with 5 notches on S. & 1 on N. edges; from which
- Fir, 40 in. dia., bears N.45°E., 71 lks. dist.,
marked T 20 S R 8 W S 6 B T.
- Fir, 48 in. dia., bears S.62°E., 30 lks. dist.,
marked T 20 S R 8 W S 7 B T.
- Fir, 36 in. dia., bears S.57°W., 32 lks. dist.,