

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20 S., R. 8 W.

CHAINS

marked T 20 S R 9 W S 12 B T.

Fir, 10 in. dia., bears N.66°W., 18 lks. dist.,

marked T 20 S R 9 W S 1 B T.

Oct. 4, 1883.

North between secs. 1 & 6.

V.20°E.

Along West slope of hill.

28.00 Cross spur; descend.

37.00 Branch, 2 lks. wide, flows West; ascend.

40.00 Set post, 4 in. dia., 4 ft. long, with marked stone, 12 in. in ground, for 1/4 sec. cor., marked 1/4 S on W. face; from which

Fir, 18 in. dia., bears S.19°E., 14 lks. dist.,

marked 1/4 S B T.

Fir, 12 in. dia., bears S.70°W., 36 lks. dist.,

marked 1/4 S B T.

45.00 Cross ridge; descend.

64.00 Creek, 8 lks. wide, flows West; ascend.

80.00 Set post, 6 in. dia., 4 ft. long, 24 in. in ground, for cor. to Town. 19 & 20 S., R. 8 & 9 W., marked T 19 S S 31 on NE., R 8 W S 6 on SE., T 20 S S 1 on SW., R 9 W S 36 on NW. faces, with 6 notches on each edge; from which

Fir, 30 in. dia., bears N.48°E., 23 lks. dist.,

marked T 19 S R 8 W S 31 B T.

Fir, 20 in. dia., bears S.7°E., 43 lks. dist.,

marked T 20 S R 8 W S 6 B T.

Hemlock, 8 in. dia., bears S.81°W., 37 lks. dist.,

marked T 20 S R 9 W S 1 B T.

Fir, 30 in. dia., bears N.53°W., 78 lks. dist.,

marked T 19 S R 9 W S 36 B T.

Oct. 5th, 1883.