

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 9 W.
Survey by Wm. Thiel under Contract 567 dated Feb. 16, 1891.

CHAINS

I begin at the cor. to secs. 33 and 34, T. 20 S., R. 9 W. and Secs. 3 and 4, T. 21 S., R. 9 W., which is a post, 4 in. sq., marked T 20 S S 34 on NE., R 9 W S 3 on SE., T 21 S S 4 on SW., S 33 on NW. faces, with 3 notches on the E. and W. edges; from which

A hemlock, 15 ins. diam., bears N.46°E., 67 lks. dist., marked T 20 S R 9 W S 34 B T.

A hemlock, 8 in. in dia., bears S.21°E., 36 lks. dist., marked T 21 S R 9 W S 3 B T.

An alder, 16 ins. diam., bears S.63½°W., 67 lks. dist., marked T 21 S R 9 W S 4 B T.

A fir, 30 ins. diam., bears N.14°W., 46 lks. dist., marked T 20 S R 9 W S 33 B T.

Thence I run

East, on South boundary of Sec. 34.

Var. 20°8'E.

Through a timber flat, nearly level.

0.46 A cedar, 36 ins. in diam., which I marked with 2 notches on E. & W. sides.

1.50 Begin ascent of a West slope.

13.00 Change ascent to a SW. slope.

19.50 Top of spur, bears SW. and NE.; begin descent. +450

27.60 A canyon, course NW., with a small stream of water; begin ascent. -120

37.50 Top of a flat ridge, course E. & W. +360

40.00 A fir, 36 ins. diam., which I mark ¼ S on N. face, for ¼ sec. cor.; from which

A fir, 16 ins. diam., bears S.88°W., 72 lks. dist., marked ¼ S B T.

A cedar, 12 ins. diam., bears N.46°E., 70 lks. dist., marked ¼ S B T.

Along top of timber ridge.

51.00 Begin descent of a burnt timber N. slope.

63.50 Descent is very steep; enter green timber.