

South Bdy. of T. 20 S., R. 9 W.

CHAINS 76.00	A timber flat.	
79.00	Again steep descent.	
80.00	A fir, 18 ins. diam., which I mark for corner to secs. 35, 2, 3, and 34, T 20 S S 35 on NE., R 9 W S 2 on SE., T 21 S S 3 on SW., S 34 on NW. sides, with 2 notches on E. and 4 notches on W. sides; from which	
	An alder, 15 ins. in diam., bears N.47°E., 56 lks. dist., marked T 20 S R 9 W S 35 B T.	
	A maple, 12 ins. diam., bears S.28°E., 33 lks. dist., marked T 21 S R 9 W S 2 B T.	
	A fir, 15 ins. diam., bears S.25½°W., 41 lks. dist., marked T 21 S R 9 W S 3 B T.	
	A fir, 42 in. diam., bears N.88°W., 78 lks. dist., marked T 20 S R 9 W S 34 B T.	
<hr/>		
	East, on south boundary of Sec. 35.	
	Var. 20° 2' E.	
	Continue steep descent.	
2.10	Scare creek, 40 lks. wide, course N.	
2.60	Begin steep ascent of a cliff.	
9.00	Enter green fir timber.	
17.50	Top of ridge, bears N. and S.; begin descent of N. slope.	+420
22.00	Nearly level; begin ascent, through fine old fir timber.	-50
28.25	Ascend N. slope of mountain.	
37.00	Begin descent of SE. slope.	+100
40.00	Set a post (maple), 5 ft. long, 4 ins. square, 24 ins. in the ground, marked ¼ S on N. face, for ¼ sec. cor.; from which	
	An alder, 8 ins. diam., bears S.69½°W., 40 lks. dist., marked ¼ S B T.	
	A maple, 4 ins. diam., bears N.17½°E., 5 lks. dist., marked ¼ S B T.	
	This post stands between 4 windfalls.	
42.00	Change the descent to E. slope.	
53.50	A canyon, course SE.	