

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 9 W.

CHAINS

- 62.20 A canyon, course S.; begin to ascend.
Sept. 4, 1891.
- 71.25 Very steep ascent.
- 74.00 A flat burnt timber ridge, bears NW. and SE.
- 80.00 A fir stump, $4\frac{1}{2}$ ft. above ground and 8 ins. in diam., which I marked T 20 S S 36 on NE., R 9 W S 1 on SE., T 21 S S 2 on SW., S 35 on NW. faces, with 1 notch on E. and 5 notches on W. sides, for cor. to secs. 35, 36, 1 and 2; from which
A fir, 36 ins. diam., bears N. $80\frac{1}{2}^{\circ}$ E., 170 lks. dist., marked T 20 S R 9 W S 36 B T.
A fir, 36 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ E., 2.10 chs. dist., marked T 21 S R 9 W S 1 B T.
An alder, 3 ins. diam., bears S. 60° W., 95 lks. dist., marked T 21 S R 9 W S 2 B T.
An alder, 4 ins. diam., bears N. 5° W., 5 lks. dist., marked T 20 S R 9 W S 35 B T.
-
- East, on south boundary of Sec. 36.
Var. $20^{\circ} 8' E$,
Through a nearly level flat filled with burnt timber, which is down.
- 3.00 Begin descent of E. slope, thickly set by small alders.
- 9.80 Gulch, course S.; begin ascent along a S. slope, covered by fallen timber.
- 23.10 A forked fir, 72 ins. in diam., stands isolated, which I mark with 2 notches on the E. and W. sides.
- 33.25 Begin steep descent.
- 36.60 A canyon, course S.
- 40.00 Set a sandstone, 16x12x8 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; from which
A fir, 20 ins. diam., bears N. $52\frac{1}{2}^{\circ}$ W., 46 lks. dist., marked $\frac{1}{4}$ S B T.
A fir, 24 ins. diam., bears S. 89° E., 29 lks. dist., marked $\frac{1}{4}$ S B T.