

South Bdy. of T. 20 S., R. 9 W.

CHAINS		
	This cor. stands on S. slope of a rocky point.	-60
	Ascend rocky cliff.	
43.00	Enter small green fir timber.	+120
48.00	Leave fir and enter small alders.	
57.00	Burnt and fallen timber.	
62.25	Top of ridge dividing waters of Scare Creek from those of main Smith River; ridge, bears SW. and NE., a good and extensive view.	+150
	Begin steep descent of E. slope, covered by fallen timber.	
74.50	Change descent to N. slope.	
81.00	A canyon, course N.30°W.	-240
86.50	Top of spur, bears N. & S.; begin descent.	+150
98.25	Intersect E. boundary of township, 105 lks. S. of $\frac{1}{4}$ sec. corner bet. secs. 31 & 36, which is a fir, 8 ins. dia., marked $\frac{1}{4}$ S on W. face; from which A maple, 6 ins. dia., bears N.80°W., 45 lks. dist., marked $\frac{1}{4}$ S B T. A cedar, 30 ins. dia., bears S.78°E., 12 lks. dist., marked $\frac{1}{4}$ S B T.	-175
	At point of intersection I set a sandstone, 8x8x8 ins., 5 ins. in the ground, for closing cor. to sec. 36, T. 20 S., R. 9 W. and Sec. 1, T. 21 S., R. 9 W., marked C C with 6 notches on N., S. and W. edges; and raised a mound of stone, 1 $\frac{1}{2}$ ft. high, 2 ft. base, alongside. Pits impracticable.	
	Sept. 5, 1891.	
	Subdivisions of T. 20 S., R. 9 W., W.M. Survey by Wm. Thiel under Contract 567 dated Feb.16, 1891.	
	I begin at the cor. to secs. 34, 35, 2 and 3, Tps. 20 & 21 S., R. 9 W; thence I run parallel to range line.	
	N.0°3'E., bet. secs. 34 and 35.	
	Var.20°1'E.	
	Descend NE. slope.	
7.60	Scare Creek, 40 lks. wide, course N.10°W.; ascend slightly West slope.	