

Subdivisions of T. 20 S., R. 9 W.

CHAINS

A fir, 8 ins. diam., bears N.27½°E., 18 lks. dist.,
marked T 20 S R 9 W S 27 W C B T.

A fir, 12 ins. diam., bears S.66½°E., 30 lks. dist.,
marked T 20 S R 9 W S 34 W C B T.

Thence I run

N.89°42'E., on a true line, bet. secs. 27 and 34.

Var.20°8'E.

Descend E. slope of very steep bluff.

11.75 Foot of bluff; bottom. -350

12.30 Smiths River, 140 lks. wide, course N.5°W.

13.70 Enter cleared bottom.

18.80 The cor. to secs. 26, 27, 34 and 35.

I now return to the cor. of secs. 35 and 36, on the south
boundary of the township; thence I run

N.0°4'E., bet. secs. 35 and 36.

Var.20°4'E.

Ascend slightly, burnt timber flat.

4.50 Enter green fir timber.

12.00 Begin descent of NE. slope. +75

21.00 Head of canyon, course NE. -100

34.50 Top of spur, bears NE. and SW. +75

40.00 Set a sandstone, 10x8x8 ins., 7 ins. in the ground, for
¼ sec. cor., marked ¼ on W. face; and raised a mound of
stone, 1½ ft. high, 2 ft. base, alongside. Pits im-
practicable.

62.00 Top of spur, bears NE. & SW.; begin descent.

75.20 A canyon, course E.; leave green fir timber; enter burnt
timber, slightly ascending.

80.00 Set a post, 5 ft. long, 6 ins. square, 18 ins. in the
ground, for cor. to secs. 26, 25, 35, and 36, marked
T 20 S S 25 on NE., R 9 W S 36 on SE., S 35 on SW., S
26 on NW. faces, with 1 notch on S. and E. edges; from
which

A fir, 30 ins. dia., bears N.46°E., 112 lks. dist.,