

Subdivisions of T. 20 S., R. 9 W.

CHAINS

At point of intersection I set a sandstone, 10x8x7 ins., 7 ins. in the ground, for closing corner to secs. 25 and 36, marked C C with 1 notch on S. and 5 notches on N. edges; and raised a mound of stone, 1½ ft. high and 2 ft. base alongside. Pits impracticable.

Sept. 9th, 1891.

From witness cor. to secs. 19, 20, 29 and 30, which is a cedar, 54 ins. dia. and marked S 29 on E. and S 30 on West side and stands N. 13.45 chs. of ¼ sec. cor. bet. secs. 29 and 30, I run

N.0°1'E., bet. secs. 29 and 30.

Var. 20°8'E.

53.60 A canyon, course S.5°W.; ascend E. slope.

64.20 A canyon, course S.10°E.; ascend W. slope.

+150

80.00 Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 19, 20, 29 and 30, marked T 20 S S 20 on NE., R 9 W S 29 on SE., S 30 on SW., S 19 on NW. faces, with 2 notches on S. and 5 notches on E. edges; from which

+250

A fir, 30 ins. diam., bears N.27°E., 39 lks. dist., marked T 20 S R 9 W S 20 B T.

A fir, 40 ins. diam., bears S.51°W., 75 lks. dist., marked T 20 S R 9 W S 30 B T.

A fir, 30 ins. diam., bears S.21°E., 193 lks. dist., marked T 20 S R 9 W S 29 B T.

A fir, 48 ins. diam., bears N.52°W., 34 lks. dist., marked T 20 S R 9 W S 19 B T.

S.89°15'W., on random line, bet. secs. 19 and 30.

Var. 20°7'E.

40.00 Set temporary ¼ sec. cor.

80.10 Intersect W. boundary of township, 24 lks. S. of cor. to secs. 19, 30, 24 and 25.

Thence I run