

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

ground, for cor. to secs. 20, 21, 28 and 29, marked
T 20 S S 21 on NE., R 9 W S 28 on SE., S 29 on SW., S
20 on NW. faces, with 2 notches on S. and 4 notches on
E. edges; from which

A fir, 30 ins. diam., bears N.24°E., 60 lks. dist.,
marked T 20 S R 9 W S 21 B T.

A fir, 24 ins. diam., bears S.68°E., 54 lks. dist.,
marked T 20 S R 9 W S 28 B T.

A fir, 18 ins. diam., bears S.64°W., 41 lks. dist.,
marked T 20 S R 9 W S 29 B T.

A fir, 5 ins. diam., bears N.34½°W., 55 lks. dist.,
marked T 20 S R 9 W S 20 B T.

N.89°28'W., on random line, bet. secs. 20 and 29.

Var.20°7'E.

40.00 Set temporary ¼ sec. cor.

80.24 Intersect N. and S. line, 30 lks. N. of cor. to secs. 19,
20, 29, and 30.

Thence I run

S.89°41'E., on true line, between secs. 20 and 29.

Var.20°2'E.

Ascend slightly W. slope,

2.50 Top of spur, bears N. & S.; along S. slope of same. +60

27.00 A canyon, course S.; begin ascent. -120

40.12 Set a post, 3 ft. long, 3 ins. square, 18 ins. in the
ground, for ¼ sec. cor., marked ¼ S on N. face; from
which

A fir, 4 ins. diam., bears N.25°W., 37 lks. dist.,
marked ¼ S B T.

A vinemaple, 3 ins. dia., bears S.3°E., 19 lks. dist.,
marked ¼ S B T.

Along S. slope of ridge.

56.25 Begin descent.

60.80 Johnson Creek, 25 lks. wide, course SE.; begin ascent of -280
spur.