

Subdivisions of T. 20 S., R. 9 W.

CHAINS
80.24

The cor. to secs. 20, 21, 28 and 29.

Sept. 13th, 1891.

I now return to cor. to secs. 19, 20, 29 and 30; thence

I run

N.0°1'E., bet. secs. 19 and 20.

Var.20°8'E.

Ascend W. slope.

- 6.25 Ridge, bears SW. and NE.; begin descent. +75
- 12.50 Steep descent.
- 19.50 A canyon, course NE.; begin ascent. -150
- 26.00 Top of spur, bears NE. and SW. +125
- 37.25 A canyon, course E. -90
- 40.00 Set a sandstone, 10x10x6 ins., 7 ins. in the ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raised a mound
of stone, $1\frac{1}{2}$ ft. high and 2 ft. base, alongside. Pits
impracticable.
- 52.50 A branch, 5 lks. wide, course E. +60
- 57.75 A branch, 3 lks. wide, course SE.; begin ascent of S. -25
slope.
- 80.00 Set a sandstone, 24x18x6 ins., 18 ins. in the ground, +125
for cor. to secs. 17, 18, 19 and 20, marked with 3
notches on S. and 5 notches on E. edges; from which
A fir, 24 ins. diam., bears N.62 $\frac{1}{2}$ °E., 14 lks. dist.,
marked T 20 S R 9 W S 17 B T.
A fir, 30 ins. diam., bears S.58°E., 38 lks. dist.,
marked T 20 S R 9 W S 20 B T.
A fir, 40 ins. diam., bears S.62°W., 16 lks. dist.,
marked T 20 S R 9 W S 19 B T.
A fir, 32 ins. diam., bears N.89°W., 40 lks. dist.,
marked T 20 S R 9 W S 18 B T.

S.89°25'W., on random line, bet. secs. 18 and 19.

Var.20°3'E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.