

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS		
80.44	Intersect West bdy. of Tp., 48 lks. S. of cor. to secs. 18, 19, 13 & 24.	
	Sept. 14th, 1891.	
	Thence I run	
	N.89°46'E., on true line, bet. secs. 18 & 19.	
	Var.20°8'E.	
	Ascend S. slope, through dead fir timber.	
9.00	Top of spur, bears N. & S.; descend.	+150
17.50	A canyon, course S.	-290
18.50	Top of a spur, bears N. & S.	+60
19.25	A canyon, course S.	
24.25	Top of spur, bears N. & S.	+100
30.40	A canyon, course S.; ascend S. slope.	-120
38.00	Change ascent to N. slope.	
40.22	Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which	+120
	A fir, 42 ins. diam., bears N.36°E., 17 lks. dist., marked $\frac{1}{4}$ S B T.	
	A fir, 33 ins. diam., bears S.62 $\frac{1}{2}$ °W., 37 lks. dist., marked $\frac{1}{4}$ S B T.	
	This post stands near summit of butte.	
	Descending.	
44.75	A canyon, course NE.	-110
46.50	Top of ascent.	+70
52.25	A canyon, course N.; descend a NE. slope.	-275
66.10	Johnson Creek, 10 lks. wide, course S.; begin ascent.	-50
71.00	Top of ascent; begin descent.	+75
77.00	Begin ascent.	-60
80.44	The cor. to secs. 17, 18, 19 & 20.	
<p>N.0°1'E., bet. secs. 17 and 18.</p> <p style="text-align: right;">Var.20°5'E.</p> <p>Ascend S. slope.</p>		
9.00	Top of ridge, bears SW. & NE.; begin descent of NW. slope.	+200