

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

7, 18, 12 and 13.

Thence I run

N.89°29'E., on true line, bet. secs. 7 and 18.

Var.20°2'E.

Descend along S. slope.

- 5.00 Enter a timber flat, bears N. -90
- 19.75 Very steep descent.
- 24.25 A branch, 5 lks. wide, course S., below junction of 2
canyons; begin steep ascent.
- 29.50 Change ascent to a N. slope.
- 37.50 Top of a spur, bears N. & S.; descend S. slope. +400
- 40.18 A vine maple, 3 ins. dia., which I marked for $\frac{1}{4}$ sec. cor.,
 $\frac{1}{4}$ S on N. face; from which
A fir, 36 ins. dia., bears S.76°E., 100 lks. dist.,
marked $\frac{1}{4}$ S B T.
A fir, 36 ins. diam., bears N.66 $\frac{1}{2}$ °W., 12 lks. dist.,
marked $\frac{1}{4}$ S B T.
- Ascend S. slope.
- 46.25 Top of ridge, bears N. & S.; begin steep descent of E. +50
slope.
- 52.75 A canyon, course N.; begin ascent of N. slope. -175
- 59.50 Top of spur, bears N. & S.; begin steep descent. +100
- 65.10 Johnson Creek, 5 lks. wide, course S.; begin ascent of -160
a point.
- 70.25 A canyon, course W. +75
- 72.25 Leave same and begin ascent of N. slope.
- 80.36 The cor. to secs. 7, 8, 17 and 18.

Sept. 16th, 1891.

I return now to cor. to secs. 20, 21, 29 and 28; thence

I run

N.0°2'E., bet. secs. 20 and 21.

Var.20°8'E.

- 3.00 A canyon, course W.; begin ascent. -60
- 7.25 Top of a spur, bears E. & W.; begin steep descent. +120