

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS		
	A barberry, 6 ins. dia., bears S.68°E., 21 lks. dist., marked $\frac{1}{4}$ S B T.	
	A fir, 15 ins. diam., bears N.88°W., 90 lks. dist., marked $\frac{1}{4}$ S B T.	
41.80	A canyon, course S.80°W.; begin descent along N. slope.	-15
46.20	Same canyon, course N.; begin ascent of W. slope.	-40
54.50	Top of spur, bears N. & S.; begin descent of N. slope.	+120
61.10	A canyon, course N.30°W.; steep ascent.	-140
68.00	Top of dividing ridge, bears SE. & NW.; very steep descent through windfalls.	+200
75.60	A canyon, course N.; begin ascent.	-280
77.75	Top of spur, bears N. & S.; begin steep descent.	+75
79.90	A canyon, course N.	-90
80.62	The cor. to secs. 16, 17, 20 and 21.	+25
<p>N.0°2'E., bet. secs. 16 and 17. Var.20°4'E. Along W. slope, slightly ascending.</p>		
8.00	Top of spur, bears N. & S.; begin descent.	+25
11.50	A canyon, course NE.; begin ascent.	-90
27.00	Top of spur, bears SE. and NW.	+150
31.25	A branch, 2 lks. wide, course SE.	-120
40.00	Set a sandstone, 10x9x6 ins., 7 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raised a mound of stone alongside. Pits impracticable.	+80
Line runs on E. slope of dividing ridge.		
61.00	Cross top of ridge to W. slope.	
76.00	Top of ridge; along E. slope.	
80.00	A barberry, 5 ins. in dia., which I marked for cor. to secs. 16, 17, 8 and 9, T 20 S S 9 on NE., R 9 W S 16 on SE., S 17 on SW., S 8 on NW. face, with 4 notches on S. and E. edges; from which A fir, 48 ins. diam., bears N.89°E., 190 lks. dist., marked T 20 S R 9 W S 9 B T.	