

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS		
	down; begin descent.	
80.44	The cor. to secs. 8, 9, 16 and 17. Sept. 19th, 1891.	-60
	I return to cor. to secs. 21, 22, 27, and 28 and trace line to witness post between secs. 21 and 28; from which A maple, 36 ins. dia., bears S., 12 lks. dist., marked T 20 S R 9 W S 28 B T. and stands 13.15 chs. West of corner. Thence I run S.89°21'W., on random line, bet. secs. 21 and 28. Var.20°8'E.	
40.00	Set temporary $\frac{1}{4}$ sec. corner.	
80.00	Intersect N. and S. line, 42 lks. S. of cor. to secs. 20, 21, 28, and 29. N.89°39'E., on true line, bet. secs. 21 and 28. Var.20°2'E.	
2.25	Top of ridge, bears SW. and NE.	+50
9.50	A canyon, course S.	-150
16.25	Top of spur, bears SW. and NE.	+100
21.00	A canyon, course SW.	-80
27.75	Top of ridge, bears SW. and NE.; begin descent.	+100
40.00	Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which An alder, 10 ins. diam., bears N.86 $\frac{1}{2}$ °E., 63 lks. dist., marked $\frac{1}{4}$ S-B T. A maple, 30 ins. in dia., bears S.70°W., 50 lks. dist., marked $\frac{1}{4}$ S B T.	-240
40.75	Rachel Creek, 3 lks. wide, course S.10°W.; begin ascent.	-50
43.75	Top of ridge, bears SW. and NE.	+120
53.25	A canyon, course SE.	-170
56.00	Top of spur, bears SE. & NW.; begin descent of East slope.	+75