

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

S. and 2 notches on E. sides, for cor. to secs. 9, 10, 15 & 16; from which

A fir, 36 ins. diam., bears N.71°E., 46 lks. dist., marked T 20 S R 9 W S 10 B T.

A fir, 15 ins. diam., bears S.40°E., 39 lks. dist., marked T 20 S R 9 W S 15 B T.

A fir, 40 ins. diam., bears S.9°W., 29 lks. dist., marked T 20 S R 9 W S 16 B T.

A fir, 36 ins. diam., bears N.19°W., 36 lks. dist., marked T 20 S R 9 W S 9 B T.

Sept. 24th, 1891.

S.89°56'W., on random line, bet. secs. 16 and 9.

Var.20°8'E.

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

80.72 Intersect N. and S. line, 32 lks. S. of cor. to secs. 8, 9, 16, and 17.

S.89°50'E., on true line, bet. secs. 16 and 9.

Var.20°2'E.

Descend E. slope.

8.00 Enter a vine maple flat, bears N. & S.

-120

10.00 Leave same; begin steep descent.

12.60 A canyon & branch, 2 lks. wide, course NE.; begin to ascend a N. slope.

-100

22.00 Top of rise; begin to descend.

+275

27.50 A canyon, course NE.; begin ascent.

-75

29.00 Top of ascent; begin to descend.

+90

35.20 Coon Creek, 8 lks. wide, course S.10°E.

-125

Begin to ascend S. slope.

38.50 Cross canyon, course S.75°E.; begin to ascend N. slope.

+50

40.36 Set a sandstone, 12x10x7 ins., 8 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on N. face; from which

+50

A fir, 42 ins. dia., bears S.16°W., 13 lks. dist., marked  $\frac{1}{4}$  S B T.

A fir, 16 ins. diam., bears N.5°W., 12 lks. dist.,