

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

	marked $\frac{1}{4}$ S B T.	
	Keep ascending steep N. slope of ridge.	
54.00	Top of ridge, bears N. and S.; begin descent of E. slope.	+450
63.50	A canyon, course SW.; begin ascent of SW. slope.	-200
80.72	The cor. to secs. 9, 10, 15, and 16.	+90

Sept. 25th, 1891.

N.0°3'E., bet. secs. 26 and 27.

Va.20°8'E.

	Ascend W. slope of mountain.	
9.50	Top of spur, bears E. & W.; begin descent of steep W. slope.	+125
18.00	A branch, 2 lks. wide, course SW.; begin steep ascent.	-200
22.00	The ascent moderates.	
27.50	Top of a burnt timber flat; green fir timber bears E.	+240
40.00	Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which	

A fir, 36 in. in dia., bears N.70°W., 39 lks. dist., marked $\frac{1}{4}$ S B T.

A fir, 24 ins. dia., bears S.32°E., 24 lks. dist., marked $\frac{1}{4}$ S B T.

Along burnt timber flat with a few green firs.

58.50	Begin descent.	+225
64.00	A canyon and Blackwells Creek, 6 lks. wide, course SW.; begin ascent.	-150
72.50	Top of rise; go along E. slope.	+120
78.00	Begin descent of N. slope.	
79.40	A canyon, course E.; begin ascent.	-75
80.00	Set a post, 5 ft. long, 5 ins. sq., 24 ins. in the ground, for cor. to secs. 22, 23, 26, and 27, marked T 20 S S 23 on NE., R 9 W S 26 on SE., S 27 on SW., S 22 on NW. faces, with 2 notches on S. and E. edges; from which	
	A maple, 12 ins. dia., bears N.83 $\frac{1}{2}$ °E., 29 lks. dist., marked T 20 S R 9 W S 23 B T.	