

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

A maple, 15 ins. diam., bears S.49½°E., 40 lks. dist., marked T 20 S R 9 W S 26 B T.

An alder, 8 ins. diam., bears S.64°W., 46 lks. dist., marked T 20 S R 9 W S.27 B T.

A fir, 24 ins. diam., bears N.50°W., 180 lks. dist., marked T 20 S R 9 W S 22 B T.

Sept. 26th, 1891.

West, on a random line, between secs. 22 and 27.

Va.20°8'E.

40.00 Set temporary ¼ sec. cor.

80.72 Intersect 36 lks. S. of cor. to secs. 21, 22, 27, and 28. S.89°45'E., on true line, bet. secs. 22 and 27.

Va.21°1'E.

Along N. slope, through a dense growth of young firs.

7.00 A canyon & branch, 2 lks. wide, course N.60°W. -50

10.00 Top of a burnt timber flat, bears N. & S. +40

24.00 Across same canyon above, course S.60°W.; thence along N. slope. -20

38.00 Top of rise. +60

40.36 Set post, 48 ins. long, 4 ins. square, 24 ins. in the ground, for ¼ sec. cor., marked ¼ S on N. face; from which

A fir, 48 ins. diam., bears S.64½°W., 300 lks. dist., marked ¼ S B T.

A fir, 36 ins. diam., bears N.88°E., 575 lks. dist., marked ¼ S B T.

48.25 A canyon, course S. -35

53.80 A canyon, course S.; enter green fir timber. -60  
Begin steep ascent.

58.10 A gulch, course SW. +50

68.75 Top of ridge, bears N. & S.; enter burnt timber; begin a steep descent of S. slope N. of a canyon. +240

80.72 The cor. of secs. 22, 23, 26, and 27. -120